

CUTTING/WASHING ECO 2000

Compact model: Designed for sandy soil that is not very sticky

Options: Input tray, recycling unit

FEATURES

- Plastic mesh belt, 50% perforated, equipped
 - with a mobile stop.Double washing ramp: high and low.
 - 24 sprayers with ceramic nozzles.

OPERATION

$\mathbf{O}^{\mathbf{O}}$

- Fed by simply spreading the asparagus.
- The same belt carries the asparagus from input to manual sorting.
- Before cutting, the asparagus is transported by a 50 mm wide belt.
 - The two wheels hold the asparagus without damaging it to ensure a clean cut.
 Easy-to-adjust cutting length:
 - up to 27 cm.

MAINTENANCE



- The machine is made entirely from stainless steel.
- Low maintenance: simply grease the bearings.
 - Clean water wash.
 - The saw blade should be changed according to wear.

Power supply: 220 V, single phase
Total electric power: 1 kW

TECHNICAL FEATURES

- Water inlet: 25 mm diameterWater outlet: 100 mm diameter
 - Water consumption: 3 m3/h at 4 bars

SIZE

• Length: 5.70 m (also available with an extended sorting area)

- Width: 1 m
- Height: 1.30 m
- Weight: 200 kg



www.besnard-ste.fr

[▶] La Masselière - 72200 Bazouges Sur Le Loir 📞 : +33 (0)2 43 94 09 82 📙 : +33 (0)2 43 45 96 38 @ : contact®besnard-ste.fr

 With 3 operators (2 at input and + 1 at output): 150 to 300 kg/h, depending on the average size of the asparagus.